



Closed Body Turnbuckles M Series Jaw-Jaw

Product information

General:

- Standard hot dip galvanized.
- Factory supplied with locking nuts.
- Testing on request (at additional costs).
- Bolt secured with nut and split pin.
- Straight or in-line pull only.
- MBL equals 5x WLL.

Part Code	WLL ton	Take up mm	Thread	MBL ton	L min. mm	L max. mm	A mm	P mm	U mm	V mm	W mm	Weight kg
11.50420003011A	0.3	102	M8	1.5	203	305	127	6	21	9	9	0.2
11.50420005011A	0.5	110	M10	2.5	245	355	160	8	21	9	11	0.3
11.50420007011A	0.7	180	M12	3.5	345	525	230	10	35	13	19	0.8
11.50420012011A	1.2	170	M16	6	395	565	230	12	50	16	21	1.4
11.50420015011A	1.5	160	M20	7.5	395	555	230	16	46	18	21	2.2
11.50420022011A	2.2	226	M22	11	476	702	305	20	60	20	25	3.5
11.50420032011A	3.2	280	M24	16	580	860	360	22	63	24	30	4.1
11.50420038011A	3.8	270	M27	19	600	870	356	22	63	24	31	4.5
11.50420050011A	5	280	M33	25	650	930	385	24	74	30	38	6.4
11.50420063011A	6.3	230	M36	31.5	680	910	385	30	85	30	48	11
11.50420070011A	7	279	M39	35	670	949	407	34	90	32	47	11
11.5.020085011A	8.5	240	M45	42.5	780	1,020	410	35	120	43	50	19
11.50420100011A	10	234	M48	55	743	977	407	43	121	46	51	22
11.50420126011	12.6	340	M56	63	862	1,202	500	52	122	60	65	39
11.50420160011	16	355	M64	80	925	1,280	540	60	130	65	70	48

Blueprint

