

## STOBITEX Wear Protection Sleeve PU-1/single

### Product information



Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as double sided sheathes, STOBITEX Wear Protection Sleeve PU-2/double side.

**Material:** Polyurethane.

**Temperature range:** Approx. -30° up to +70°C, short expose to approx. +90°C.

Part code	Size	Inside width mm	Height mm	For 2 layer lifting mm	For 4 layer lifting mm	For roundslings ton	Weight kg/m
12.4000200020	50	40	10	30	-	-	0.85
12.4000200030	50	40	20	-	30	-	0.9
12.4000200060	70	60	12	50	-	-	1.25
12.4000200061	70	60	17	-	50	-	1.3
12.4000200070	80	70	12	60	-	-	1.3
12.4000200090	80	70	24	-	60	-	1.35
12.4000200095	85	75	12	-	-	1	1.35
12.4000200110	95	85	24	-	-	2	1.5

12.4000200120	110	100	12	90	-	-	1.55
12.4000200130	110	100	17	-	-	3	1.6
12.4000200140	110	100	24	-	90	-	1.6
12.4000200190	145	135	12	120	-	-	2
12.4000200200	145	135	24	-	120	-	2.1
12.4000200240	170	160	12	150	-	-	2.3
12.4000200250	170	160	17	-	-	6	2.4
12.4000200260	170	160	24	-	150	-	2.4
12.4000200280	200	190	12	180	-	-	2.6
12.4000200290	200	190	17	-	-	8	2.65
12.4000200300	200	190	24	-	180	-	2.7
12.4000200320	230	220	36	-	-	10	3.5
12.4000200340	260	250	15	240	-	-	3.9
12.4000200360	290	280	30	-	-	15	4.4
12.4000200370	330	320	15	300	-	-	4.4
12.4000200380	330	320	30	-	300	-	4.8
12.4000200390	330	320	45	-	-	20	5.3

## Blueprint

