



## Eye Self Locking UXLO, Green Pin®

### Product information

The Green Pin® Self-Locking Hook E is a grade 10 eye self-locking hook. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The eye of the hook can be connected to grade 10 chain with a connecting link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Self-Locking Hook E is available in a range to suit 6 mm up to 20 mm grade 10 chain.

**Certification:** at no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or Declaration of Conformity

**Material:** alloy steel, quenched and tempered

**Temperature range:** -40°C up to +200°C

**Finish:** painted blue

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	For chain diameter inch	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
11.15UXLO0	6	1.4	7/32	111	24	32	16	26	47	77	147	11	7	0.51
11.15UXLO1	8	2.6	5/16	134	29	43	23	29	57	92	176	14	7	0.91
11.15UXLO2	10	4	3/8	168	35	47	32	35	69	111	219	17	10	1.79
11.15UXLO3	13	6.8	1/2	199	46	61	37	45	87	142	264	20	13	3.36
11.15UXLO4	16	10.3	5/8	247	59	74	43	56	111	185	328	26	16	7

## Blueprint

