

Steel wire rope veropro 10

Product information



Wire rope construction: veropro 10 is a very flexible 10-strand, non-rotation resistant rope with compacted strands and a rope core covered with a plastic layer.

Features:

- Very high breaking strength
- Very stable rope structure and achieves excellent bending fatigue results
- Offers excellent resistance to crushing and abrasion
- Perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.11.**

Marking: According to standard

Standard: EN 12385-4


Note: veropro 10 may not be used with a swivel.

Fill factor: 0.683

RCN: 11

Tolerance Ø: +2% to +4%

Overhead cranes



Mobile port crane



Offshore crane



Loading crane



Crawler crane



Container crane



Tower crane



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m
01.G13VP1620H	62	2,160	-	-	Galvanized	-
01.B28VP1300G	30	1,960	-	-	Bright	-
01.B28VP1320G	32	1,960	-	-	Bright	-
01.B28VP1340G	34	1,960	-	-	Bright	-
01.B28VP1360G	36	1,960	-	-	Bright	-
01.B28VP1380G	38	1,960	-	-	Bright	-
01.B28VP1400G	40	1,960	-	-	Bright	-
01.B28VP1420G	42	1,960	-	-	Bright	-
01.B28VP1440G	44	1,960	-	-	Bright	-
01.B28VP1460G	46	1,960	-	-	Bright	-
01.B28VP1480G	48	1,960	-	-	Bright	-
01.B28VP1500G	50	1,960	-	-	Bright	-
01.B28VP1520G	52	1,960	-	-	Bright	-
01.B13VP1540G	54	1,960	-	-	Bright	-
01.B28VP1560G	56	1,960	-	-	Bright	-
01.B28VP1580G	58	1,960	-	-	Bright	-
01.B28VP1600G	60	1,960	-	-	Bright	-
01.B28VP1640G	64	1,960	-	-	Bright	-
01.B28VP1660G	66	1,960	-	-	Bright	-
01.B28VP1680G	68	1,960	-	-	Bright	-
01.B28VP1700G	70	1,960	-	-	Bright	-