



Wire Rope Lifting Sling WLS-115

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Soft eye in one end and eyehook with safety latch in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

Part Code	WLL ton
WLS11503	0.12
WLS11504	0.21
WLS11505	0.32
WLS11506	0.47
WLS11508	0.82
WLS11509	1.04
WLS11510	1.28
WLS11511	1.55

WLS11512	1.84
WLS11513	2.17
WLS11514	2.51
WLS11516	3.3
WLS11518	4.1
WLS11520	5.1
WLS11522	6.2
WLS11524	7.38
WLS11526	8.66
WLS11528	10.04
WLS11532	13.12
WLS11536	16.59
WLS11540	20.56
WLS11544	24.78
WLS11548	29.55
WLS11552	34.69

Technical data