



Trec LH Mobile shelf ladder

Product information

General: For easy rolling along the shelves: The solution is equipped with guide rails and self-locking sprung castors and can be customised to the desired height. In case of order, please provide the distance from the floor to the top edge of the rail.

Features and benefits:

- Both the top of the ladder and the self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.
- When not in use, the ladder can be stowed vertically on the shelf to save space.

Available in 3 Types:

1. **Comfortstep Trec LH** (ladder width 380 mm)
Screwed tread with padded front edge.
Base length = vertical height of the guide rail \times 0.404
2. **Saferstep Trec LH** (ladder width 420 mm)
Edge-formed tread with ZARGES Safer Step Technology.
Base length = vertical height of the guide rail \times 0.364
3. **Stella Trec LH** (ladder width 490 mm)
edge-formed wide rung.
Base length = vertical height of the guide rail \times 0.268

Accessories Optional (to be ordered separately):

A1: 99.XX40370 Aluminium alloy tube, \varnothing 30 mm, 3000 mm long, anodised

A2: 99.XX41457 Aluminium alloy intermediate bracket.

A3: 99.XX41457 Aluminium alloy bracket with stop on the right

A4: 99.XX41457 Aluminium alloy bracket with stop on the left.

Rail systems: One intermediate bracket is required for every approx. 1.00 m of tubing.

Material: Aluminium

Marking: According to standard

Finish: anodised

Standard: EN 131 Cat. Professional

Note: Max. load 150 kg.

Part Code	Type	from/to maximum vertical hook-on height m	no. of rungs	no. of treads
99.XX0041412	1: Comfortstep Trec LH	1.84–2.08	-	6
99.XX0041413	1: Comfortstep Trec LH	2.09–2.33	-	7
99.XX0041414	1: Comfortstep Trec LH	2.34–2.58	-	8
99.XX0041415	1: Comfortstep Trec LH	2.59–2.83	-	9
99.XX0041416	1: Comfortstep Trec LH	2.84–3.08	-	10
99.XX1141356	2: Saferstep Trec LH	1.67–2.16	-	6
99.XX1141358	2: Saferstep Trec LH	2.17–2.67	-	8
99.XX1141360	2: Saferstep Trec LH	2.68–3.20	-	10
99.XX1141362	2: Saferstep Trec LH	3.21–3.72	-	12
99.XX1141364	2: Saferstep Trec LH	3.73–4.25	-	14
99.XX1141511	3: Stella Trec LH	1.73-2.26	6	-
99.XX1141512	3: Stella Trec LH	2.27-2.80	8	-
99.XX1141513	3: Stella Trec LH	2.81-3.34	10	-
99.XX1141514	3: Stella Trec LH	3.35-3.88	12	-
99.XX1141515	3: Stella Trec LH	3.89-4.42	14	-
99.XX0040370.	A1	-	-	-
99.XX0041457.	A2	-	-	-
99.XX0041458.	A3	-	-	-
99.XX0041459.	A4	-	-	-

Blueprint

