

Swageless Terminal with Thread

Product information



Swageless stainless thread terminal for safe, reliable and machine free self assembly.

Material: Stainless steel AISI 316.

Temperature range: -50°C to +100°C and briefly up to +200°C

Finish: High polished.

Warning: Read assembly instructions before use!



| Part Code | Rope Ø range mm | MBL ton | Thread | G thread | L1 mm | L2 mm | L3 mm | KW1 | KW2 | Weight kg/100pc |
|-------------|-----------------|---------|----------|----------|-------|-------|-------|-----|-----|-----------------|
| 10.07810305 | 3 | 0.75 | M5 Left | M5 | 79 | 58 | 42 | 10 | 12 | 4.2 |
| 10.07800305 | 3 | 0.75 | M5 Right | M5 | 79 | 58 | 42 | 10 | 12 | 4.2 |
| 10.07810306 | 3 | 0.75 | M6 Left | M6 | 85 | 63 | 47 | 10 | 12 | 4.5 |
| 10.07800306 | 3 | 0.75 | M6 Right | M6 | 85 | 63 | 47 | 10 | 12 | 4.5 |
| 10.07810406 | 4 | 1.2 | M6 Left | M6 | 92 | 63 | 47 | 12 | 14 | 5.6 |
| 10.07800406 | 4 | 1.2 | M6 Right | M6 | 92 | 63 | 47 | 12 | 14 | 5.6 |
| 10.07810408 | 4 | 1.5 | M8 Left | M8 | 102 | 72 | 57 | 12 | 14 | 6.6 |
| 10.07800408 | 4 | 1.5 | M8 Right | M8 | 102 | 72 | 57 | 12 | 14 | 6.6 |

| | | | | | | | | | | |
|-------------|----|------|-----------|-----|-----|-----|-----|----|----|-----|
| 10.07810508 | 5 | 2.18 | M8 Left | M8 | 111 | 78 | 57 | 13 | 16 | 9 |
| 10.07800508 | 5 | 2.18 | M8 Right | M8 | 111 | 78 | 57 | 13 | 16 | 9 |
| 10.07810510 | 5 | 2.18 | M10 Left | M10 | 117 | 84 | 63 | 13 | 16 | 10 |
| 10.07800510 | 5 | 2.18 | M10 Right | M10 | 117 | 84 | 63 | 13 | 16 | 10 |
| 10.07810610 | 6 | 3.5 | M10 Left | M10 | 128 | 90 | 63 | 16 | 19 | 15 |
| 10.07800610 | 6 | 3.5 | M10 Right | M10 | 128 | 90 | 63 | 16 | 19 | 15 |
| 10.07810612 | 6 | 3.7 | M12 Left | M12 | 145 | 107 | 80 | 16 | 19 | 17 |
| 10.07800612 | 6 | 3.7 | M12 Right | M12 | 145 | 107 | 80 | 16 | 19 | 17 |
| 10.07810712 | 7 | 4.7 | M12 Left | M12 | 153 | 110 | 80 | 18 | 21 | 22 |
| 10.07800712 | 7 | 4.7 | M12 Right | M12 | 153 | 110 | 80 | 18 | 21 | 22 |
| 10.07810714 | 7 | 4.7 | M14 Left | M14 | 162 | 119 | 89 | 18 | 21 | 25 |
| 10.07800714 | 7 | 4.7 | M14 Right | M14 | 162 | 119 | 89 | 18 | 21 | 25 |
| 10.07810812 | 8 | 5.1 | M12 Left | M12 | 162 | 113 | 80 | 19 | 24 | 28 |
| 10.07800812 | 8 | 5.1 | M12 Right | M12 | 162 | 113 | 80 | 19 | 24 | 28 |
| 10.07810814 | 8 | 5.6 | M14 Left | M14 | 171 | 122 | 89 | 19 | 24 | 31 |
| 10.07800814 | 8 | 5.6 | M14 Right | M14 | 171 | 122 | 89 | 19 | 24 | 31 |
| 10.07810816 | 8 | 5.6 | M16 Left | M16 | 182 | 133 | 100 | 19 | 24 | 40 |
| 10.07800816 | 8 | 5.6 | M16 Right | M16 | 182 | 133 | 100 | 19 | 24 | 40 |
| 10.07811016 | 10 | 8.3 | M16 Left | M16 | 190 | 139 | 100 | 24 | 27 | 48 |
| 10.07801016 | 10 | 8.3 | M16 Right | M16 | 190 | 139 | 100 | 24 | 27 | 48 |
| 10.07811220 | 12 | 12 | M20 Left | M20 | 227 | 159 | 120 | 27 | 32 | 79 |
| 10.07801220 | 12 | 12 | M20 Right | M20 | 227 | 159 | 120 | 27 | 32 | 79 |
| 10.07811422 | 14 | 17 | M22 Left | M22 | 264 | 191 | 140 | 30 | 36 | 124 |

| | | | | | | | | | | |
|-------------|----|----|-----------|-----|-----|-----|-----|----|----|-----|
| 10.07801422 | 14 | 17 | M22 Right | M22 | 264 | 191 | 140 | 30 | 36 | 124 |
| 10.07811624 | 16 | 21 | M24 Left | M24 | 308 | 227 | 170 | 32 | 41 | 175 |
| 10.07801624 | 16 | 21 | M24 Right | M24 | 308 | 227 | 170 | 32 | 41 | 175 |

Blueprint

