



## Stainless Steel Wire Rope SS 6x7-WSC

### Product information



**Typical applications:** Rigging, stays, controls and signalling devices.

**Material:** AISI 316.

**Marking:** According to standard

**Standard:** EN 12385-4

**Fill factor:** 0.55

General use



Stay rope



Part Code	Rope Diameter,	Steel area mm <sup>2</sup>	Min. Breaking force kN. 1570 N/mm <sup>2</sup>	Weight kg/100m
01.S10049010D	1	0.43	0.61	0.38
01.S10049015D	1.5	0.97	1.37	0.86
01.S10049018D	1.8	1.4	1.97	1.2
01.S10049020D	2	1.73	2.44	1.54
01.S10049025D	2.5	2.7	3.81	2.4
01.S10049030D	3	3.89	5.48	3.46
01.S10049040D	4	6.91	9.75	6.14
01.S10049050D	5	10.8	15.2	9.6
01.S10049060D	6	15.6	21.9	13.8
01.S10049070D	7	21.2	29.8	18.8
01.S10049080D	8	27.6	39	24.6
01.S10049090D	9	35	49.3	31.1
01.S10049100D	10	43.2	60.9	38.4
01.S10049110D	11	52.3	73.7	46.5
01.S10049120D	12	62.2	87.7	55.3
01.S10049130D	13	73	103	64.9
01.S10049140D	14	84.7	119	75.3
01.S10049150D	15	97.2	137	86.4
01.S10049160D	16	111	156	98.3
01.S10049180D	18	140	197	124
01.S10049200D	20	173	244	154