



Wire Rope Lifting Sling WLS-102

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: One end soft eye. Other end thimble. Both mechanically spliced with alu. ferrule.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

Part Code	WLL ton
WLS10203	0.12
WLS10204	0.21
WLS10205	0.32
WLS10206	0.47
WLS10208	0.82
WLS10209	1.04
WLS10210	1.28
WLS10211	1.55

WLS10212	1.84
WLS10213	2.17
WLS10214	2.51
WLS10216	3.3
WLS10218	4.1
WLS10220	5.1
WLS10222	6.2
WLS10224	7.38
WLS10226	8.66
WLS10228	10.04
WLS10232	13.12
WLS10236	16.59
WLS10240	20.56
WLS10244	24.78
WLS10248	29.55
WLS10252	34.69

Technical data