



## Wire Rope Lifting Sling WLS-175

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Master link in one end and eyehook with safety latch in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

<b>Part Code</b>	<b>WLL ton</b>
WLS17503	0.12
WLS17504	0.21
WLS17505	0.32
WLS17506	0.47
WLS17508	0.82
WLS17510	1.28
WLS17512	1.84
WLS17514	2.51
WLS17516	3.3
WLS17518	4.1
WLS17520	5.1
WLS17522	6.2
WLS17524	7.38
WLS17526	8.66
WLS17528	10.04
WLS17532	13.12
WLS17536	16.59
WLS17540	20.56
WLS17544	24.78
WLS17548	29.55
WLS17552	34.69

## Technical data