

Steel Wire Rope 6x36WS-IWRC

Product information



ISO 4309 Rope Category No: All Diameters **RCN.09**

Rope construction: 6x36WS-IWRC.

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.59

RCN: 09

Slings




Winch rope



Stay rope



Overhead cranes



Tower crane



Container crane



Mobile port crane



Offshore crane



Loading crane



Crawler crane



Piling crane



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Min. Breaking force kN.	Finish	Weight kg/100m
01.G10---080G	8	1,960	-	Galvanized	-
01.G10---090G	9	1,960	-	Galvanized	-
01.G10---100G	10	1,960	-	Galvanized	-
01.G10---110G	11	1,960	-	Galvanized	-
01.G10---120G	12	1,960	-	Galvanized	-
01.G10---130G	13	1,960	-	Galvanized	-
01.G10---140G	14	1,960	-	Galvanized	-
01.G10---160G	16	1,960	-	Galvanized	-
01.G10---180G	18	1,960	-	Galvanized	-
01.G10---190G	19	1,960	-	Galvanized	-
01.G10---200G	20	1,960	-	Galvanized	-
01.G10---220G	22	1,960	-	Galvanized	-
01.G10---240G	24	1,960	-	Galvanized	-
01.G10---260G	26	1,960	-	Galvanized	-
01.G10---280G	28	1,960	-	Galvanized	-
01.G10---300G	30	1,960	-	Galvanized	-
01.G10---320G	32	1,960	-	Galvanized	-
01.G10---340G	34	1,960	-	Galvanized	-

01.G10---360G	36	1,960	-	Galvanized	-
01.G10---380G	38	1,960	-	Galvanized	-
01.G10---400G	40	1,960	-	Galvanized	-
01.G10---420G	42	1,960	-	Galvanized	-
01.G10---440G	44	1,960	-	Galvanized	-
01.G10---460G	46	1,960	-	Galvanized	-
01.G10---480G	48	1,960	-	Galvanized	-
01.G10---500G	50	1,960	-	Galvanized	-
01.G10---520G	52	1,960	-	Galvanized	-
01.G10---540G	54	1,960	-	Galvanized	-
01.G10---560G	56	1,960	-	Galvanized	-
01.G10---580G	58	1,960	-	Galvanized	-
01.G10---600G	60	1,960	-	Galvanized	-
01.G10---640G	64	1,960	-	Galvanized	-
01.G10---680G	68	1,960	-	Galvanized	-
01.G10---720G	72	1,960	-	Galvanized	-
01.G10---760G	76	1,960	-	Galvanized	-