

GL200 Cable Grip open with 2 thimbles

Product information

General: Tool for mounting of wire ropes.

Design: Open with two thimbles.

Also available in special editions in larger sizes and stainless material.

Material: Galvanized steelwire 1960N/mm²



| Part Code | Rope Ø range mm | Length mm | Max. pullingforce kN | Thimble Ø mm |
|-------------------|--------------------|--------------|-------------------------|-----------------|
| 10.15KBZ208/1250 | 8-10 | 1,250 | 3.3 | 16 |
| 10.15KBZ210/1250 | 8-15 | 1,250 | 6.2 | 18 |
| 10.15KBZ215/1250 | 15-20 | 1,250 | 12.8 | 18 |
| 10.15KBZ220/1250 | 20-30 | 1,250 | 16 | 18 |
| 10.15KBZ230/1250 | 30-40 | 1,250 | 19.2 | 18 |
| 10.15KBZ240/1250 | 40-50 | 1,250 | 22.4 | 18 |
| 10.15KBZ250/1250 | 50-60 | 1,250 | 37.4 | 20 |
| 10.15KBZ260/1250 | 60-70 | 1,250 | 49.9 | 24 |
| 10.15KBZ270/1250 | 70-80 | 1,250 | 49.9 | 24 |
| 10.15KBZ280/1250 | 80-90 | 1,250 | 56.2 | 24 |
| 10.15KBZ290/1250 | 90-100 | 1,250 | 62.4 | 24 |
| 10.15KBZ2100/1250 | 100-115 | 1,250 | 62.4 | 24 |
| 10.15KBZ2115/1250 | 115-130 | 1,250 | 74.8 | 40 |
| 10.15KBZ2130/1250 | 130-150 | 1,250 | 74.8 | 40 |
| 10.15KBZ2150/1250 | 150-180 | 1,250 | 87.3 | 45 |
| 10.15KBZ2180/2000 | 180-210 | 2,000 | 99.8 | 45 |