

Wall Jib Crane Articulated PMA

Product information



This articulated jib crane has a very reduced headroom. His first arm can rotate 180° degrees and the second 300°. The articulated structure facilitates the movement of loads in a cluttered environment. This model is restricted to only manual rotations.

The PMA are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Option of a slowing device on each arm
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multipositions rotation lock (arm 1 only)
- Electric or manual hoist
- Outdoor use

Part code	WLL	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0
6025PMA013	0.125	125	•	•	•	•	•	•	•
6025PMA025	0.25	250	•	•	•	•	•	•	•

Technical data

Outreach (m) / Capacity (kg)	2	2,5	3	3,5	4	4,5	5
125	x	x	x	x	x	x	x
250	x	x	x	x	x	x	x