



## Swivel Jaw End Crosby G-403

### Product information

Chain swivels with out bearing. According to Federal Specification RR-C-271F.

**Material:** Hot dip Galvanized - Quenched & Tempered

**Marking:** CE-marked, WLL

**Finish:** Galvanized

**Note:** The swivels are positioning devices and are not intended to rotate under load. For load swivels, see ball bearing swivels.

**Safety factor:** 5:1

Part Code	Diameter mm	WLL ton	A mm	B mm	C mm	G mm	J mm	K mm	L mm	M mm	N mm	P mm	R mm	U mm	V mm	Weight kg
11.451016395	6	0.39	31.8	17.5	19.1	17.5	17.5	11.9	26.2	7.9	22.4	6.4	67	42.9	42.9	0.1
11.451016411	8	0.57	41.4	20.6	25.4	20.6	20.6	12.7	28.7	9.7	22.4	7.9	74.5	52	46	0.15
11.451016439	10	1.02	51	23.9	31.8	25.4	25.4	16	35.8	12.7	26.9	9.7	92	63.5	57	0.3
11.451016457	13	1.63	63.5	33.3	38.1	33.3	33.3	19.1	44.5	16	33.3	12.7	114	81	73	0.61
11.451016475	16	2.36	76	39.5	44.5	41.4	38.1	23.9	52	19.1	38.1	16	135	98.5	87.5	1.12
11.451016493	19	3.27	89	44.5	51	47.8	47.8	28.7	64.5	22.4	44.5	19.1	154	109	102	1.76
11.451016518	22	4.54	102	52	57	54	54	34	70.9	25.4	52	22.4	178	127	115	2.66
11.451016536	25	5.67	114	58.5	63.5	67	60.5	44.5	94.5	28.7	71.5	28.7	217	146	151	4.46
11.451016572	32	8.16	145	68.5	79.5	79.5	76	52	109	41.4	71.5	35.1	248	179	162	7.14
11.451016590	38	20.5	178	98.5	102	143	102	73	152	57	113	57	362	254	275	24.8

# Blueprint

