



# Roundsling Endura

## Product information

**Design:** Load carrying polyester yarn covered with “seamless” color coded extra sturdy polyester protection sleeve. Endura for heavy duty use.

**Stretch with working load:** 2-3%.  
**Length tolerance:** Nominal length (EWL) ±2%.

**Material:** Polyester. (Resistant to most acids but not strong alkalis.)  
**Marking:** According to standard, CE-marked  
**Temperature range:** -40°C up to +100°C.  
**Standard:** EN 1492-2

**Safety factor:** 7:1.

Part code	WLL ton
12.20ENDRS010.XXX	1
12.20ENDRS010.010	1
12.20ENDRS010.015	1
12.20ENDRS010.020	1
12.20ENDRS010.025	1
12.20ENDRS010.030	1
12.20ENDRS010.040	1

12.20ENDRS010.050	1
12.20ENDRS010.060	1
12.20ENDRS020.XXX	2
12.20ENDRS020.010	2
12.20ENDRS020.015	2
12.20ENDRS020.020	2
12.20ENDRS020.025	2
12.20ENDRS020.030	2
12.20ENDRS020.040	2
12.20ENDRS020.050	2
12.20ENDRS020.060	2
12.20ENDRS030.XXX	3
12.20ENDRS030.010	3
12.20ENDRS030.015	3
12.20ENDRS030.020	3
12.20ENDRS030.025	3
12.20ENDRS030.030	3
12.20ENDRS030.040	3
12.20ENDRS030.050	3
12.20ENDRS030.060	3
12.20ENDRS040.XXX	4
12.20ENDRS040.010	4
12.20ENDRS040.015	4

12.20ENDRS040.020	4
12.20ENDRS040.025	4
12.20ENDRS040.030	4
12.20ENDRS040.040	4
12.20ENDRS040.050	4
12.20ENDRS040.060	4
12.20ENDRS040.080	4
12.20ENDRS040.100	4
12.20ENDRS050.XXX	5
12.20ENDRS050.010	5
12.20ENDRS050.015	5
12.20ENDRS050.020	5
12.20ENDRS050.025	5
12.20ENDRS050.030	5
12.20ENDRS050.040	5
12.20ENDRS050.050	5
12.20ENDRS050.060	5
12.20ENDRS050.080	5
12.20ENDRS050.100	5