

## Hydraulic Hoses - Standard Hoses - H SOU

### Product information



#### Holmatro Standard hoses

- Suitable for high pressure hydraulics / max 700bar working pressure
- Anti-kink spring on both sides
- All hoses are individually tested during the production proces.
- Safety factor 4:1 - resulting in a 10 year lifespan.

#### Standard supplied with:

- Hose connection A = 3/8" NPT male
- Hose connection B = A 119 male coupler
- Already filled with oil.

#### Also available:

- Hydraulic cylinders
- Hydraulic pump units 700bar to control the cylinder(s)
- System components to complete your hydraulic system

#### Available on request:

- Different lengths.
- Other colour.

**Safety factor:** 4:1

| <b>Code</b> | <b>Size</b> | <b>Model</b> | <b>max. working pressure<br/>bar / Mpa</b> | <b>connection A</b> | <b>connection B</b> |
|-------------|-------------|--------------|--|---------------------|---------------------|
| H 1 SOU     | 1 m         | H 1 SOU      | 720 / 72                                   | 3/8" NPT male       | coupler A 119       |
| H 10 SOU    | 10 m        | H 10 SOU     | 720 / 72                                   | 3/8" NPT male       | coupler A 119       |
| H 2 SOU     | 2 m         | H 2 SOU      | 720 / 72                                   | 3/8" NPT male       | coupler A 119       |
| H 3 SOU     | 3 m         | H 3 SOU      | 720 / 72                                   | 3/8" NPT male       | coupler A 119       |
| H 5 SOU     | 5 m         | H 5 SOU      | 720 / 72                                   | 3/8" NPT male       | coupler A 119       |