



Chain Sling CSX-376 Grade 10

Product information

Design: Chain sling with master link on one end and clevis safety hook on the other end of each leg. \varnothing 19 and 22 mm chain are fitted with eye safety hooks. Other combinations possible on demand.

Dimensions: \varnothing 6–22 mm (other dimensions on demand).

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	WLL ton
11.91CSX37606XXX	3
11.91CSX37606005	3
11.91CSX37606010	3
11.91CSX37606015	3
11.91CSX37606020	3
11.91CSX37606030	3
11.91CSX37606040	3
11.91CSX37606050	3

11.91CSX37606060	3
11.91CSX37608XXX	5.3
11.91CSX37608005	5.3
11.91CSX37608010	5.3
11.91CSX37608015	5.3
11.91CSX37608020	5.3
11.91CSX37608030	5.3
11.91CSX37608040	5.3
11.91CSX37608050	5.3
11.91CSX37608060	5.3
11.91CSX37610XXX	8
11.91CSX37610005	8
11.91CSX37610010	8
11.91CSX37610015	8
11.91CSX37610020	8
11.91CSX37610030	8
11.91CSX37610040	8
11.91CSX37610050	8
11.91CSX37610060	8
11.91CSX37613XXX	14
11.91CSX37613005	14
11.91CSX37613010	14
11.91CSX37613015	14

11.91CSX37613020	14
11.91CSX37613030	14
11.91CSX37613040	14
11.91CSX37613050	14
11.91CSX37613060	14
11.91CSX37616XXX	21.2
11.91CSX37616005	21.2
11.91CSX37616010	21.2
11.91CSX37616015	21.2
11.91CSX37616020	21.2
11.91CSX37616030	21.2
11.91CSX37616040	21.2
11.91CSX37616050	21.2
11.91CSX37616060	21.2
11.91CSX37619XXX	30
11.91CSX37619005	30
11.91CSX37619010	30
11.91CSX37619015	30
11.91CSX37619020	30
11.91CSX37619030	30
11.91CSX37619040	30
11.91CSX37619050	30
11.91CSX37619060	30

11.91CSX37622XXX	40
11.91CSX37622005	40
11.91CSX37622010	40
11.91CSX37622015	40
11.91CSX37622020	40
11.91CSX37622030	40
11.91CSX37622040	40
11.91CSX37622050	40
11.91CSX37622060	40