

6x36ws+staalkern

Productinformatie



Stalkabelconstructie: 6x36ws+stk

Markering: Volgens norm

Afwerking: Standaard verzinkt

Norm: EN 12385-4

Vulfactor: 0.59

RCN: 09

Stropen-kabel




Lierkabel



Tuikabel



Bovenloop-kraan



Torenkraan



Container-kraan



Mobiele haven-kraan



Offshore kraan



Laadkraan



Rupskraan



Heikraan



Artikelnr.	Kabeldia. mm	Tensile strength N/mm ²	Minimale breekkracht kN	Afwerking	Gewicht kg/100m
01.G10---080G	8	1.960	-	Verzinkt	-
01.G10---090G	9	1.960	-	Verzinkt	-
01.G10---100G	10	1.960	-	Verzinkt	-
01.G10---110G	11	1.960	-	Verzinkt	-
01.G10---120G	12	1.960	-	Verzinkt	-
01.G10---130G	13	1.960	-	Verzinkt	-
01.G10---140G	14	1.960	-	Verzinkt	-
01.G10---160G	16	1.960	-	Verzinkt	-
01.G10---180G	18	1.960	-	Verzinkt	-
01.G10---190G	19	1.960	-	Verzinkt	-
01.G10---200G	20	1.960	-	Verzinkt	-
01.G10---220G	22	1.960	-	Verzinkt	-
01.G10---240G	24	1.960	-	Verzinkt	-
01.G10---260G	26	1.960	-	Verzinkt	-
01.G10---280G	28	1.960	-	Verzinkt	-
01.G10---300G	30	1.960	-	Verzinkt	-
01.G10---320G	32	1.960	-	Verzinkt	-
01.G10---340G	34	1.960	-	Verzinkt	-

01.G10---360G	36	1.960	-	Verzinkt	-
01.G10---380G	38	1.960	-	Verzinkt	-
01.G10---400G	40	1.960	-	Verzinkt	-
01.G10---420G	42	1.960	-	Verzinkt	-
01.G10---440G	44	1.960	-	Verzinkt	-
01.G10---460G	46	1.960	-	Verzinkt	-
01.G10---480G	48	1.960	-	Verzinkt	-
01.G10---500G	50	1.960	-	Verzinkt	-
01.G10---520G	52	1.960	-	Verzinkt	-
01.G10---540G	54	1.960	-	Verzinkt	-
01.G10---560G	56	1.960	-	Verzinkt	-
01.G10---580G	58	1.960	-	Verzinkt	-
01.G10---600G	60	1.960	-	Verzinkt	-
01.G10---640G	64	1.960	-	Verzinkt	-
01.G10---680G	68	1.960	-	Verzinkt	-
01.G10---720G	72	1.960	-	Verzinkt	-
01.G10---760G	76	1.960	-	Verzinkt	-